

Product view

Front Panel




Rear Panel



SR-HD2700U/E model rear panel photo shown.

External dimensions



Unit: inches (mm)

Specifications

Recording function		Input and Output	
HDD storage capacity	1TB	Video input/output	1.0V (p-p), 75Ω (BNC)
Video recording system	MPEG-4 AVC/H.264, MPEG-2 TS, MPEG-2 PS	Audio input/output	2 Vrms, 10 kΩ (pin jack)
Audio recording system	Dolby Digital (2ch), Linear PCM (2ch, XP mode only), MPEG1 Layer2	S-video	U Y: 1.0 V (p-p), 75Ω, C: 0.286 V (p-p), 75Ω (4-pin)
Direct recording from AUX to BD/DVD	HD/SD-SDI, HDMI, HDV/DV (i.Link) input, S-video/Video	input/output	E Y: 1.0 V (p-p), 75Ω, C: 0.3 V (p-p), 75Ω (4-pin)
Importable data format (to HDD)	MOV ⁸ , MXF ⁹ , AVCHD, HDV, DV, JPEG, BDAV, BDMV, DVD-Video, VR, SD-VIDEO (HD)	IIEEE1394 input	4-pin for HDV/DV (i.Link)
Media		Component video input	Y: 1.0 V (p-p), 75Ω (BNC), CB/CR, PB/PR: 0.7 V (p-p), 75Ω (BNC)
Blu-ray Disc	Recordable BD-R (SL/DL), BD-RE (SL/DL) ¹⁰	HDMI input/output	Output: 19-pin type A (Deep Color, x.v.Color); Input: 19-pin type A
	Playable BD-Video, BD-R (SL/DL), BD-RE (SL/DL) ¹⁰	Remote input	φ3.5mm diameter jack
DVD	Recordable DVD-R (SL/DL), DVD-RW	Serial command	RS-232C (D-sub 9-pin)
	Playable DVD-Video, DVD-R (SL/DL), DVD-RW, DVD-RAM, DVD+R (SL/DL), DVD+RW	USB terminal	USB2.0
SD card	Recordable SDHC, SD	SD memory card	SDXC ¹² , SDHC, SD
	Playable SDHC, SD	LAN terminal	10BASE-T/100BASE-TX, RJ-45
Recordable/Playable Disc Format		Accessory	
Recordable	BDAV BD-R (SL/DL), BD-RE (SL/DL) ¹⁰	Supplied accessories	AC Power Cord (US: x1, EU: x2), Infra-red Remote Control Unit "AA" battery x2
disc format	BDMV (HDMV) BD-R (SL/DL), BD-RE (SL/DL) ¹⁰	General	
	DVD-Video DVD-R (SL/DL) ¹¹ , DVD-RW	Power requirements	U: AC120V, 60Hz
	DVD-VR DVD-R (SL/DL), DVD-RW	E: AC 220V-240V, 50Hz/60Hz	
	JPEG BD-RE, SDHC, SD	Power consumption (Approx.)	42W/0.5W (Standby)
Playable	BDAV BD-R (SL/DL), BD-RE (SL/DL) ¹⁰	Temperature	Operating 41°F to 95°F (5°C to 35°C)
disc format	BDMV (HDMV) BD-Video, BD-R (SL/DL), BD-RE (SL/DL) ¹⁰	Storage	-4°F to 140°F (-20°C to 60°C)
	DVD-Video DVD-R (SL/DL), DVD-RW, DVD+R (SL/DL), DVD+RW	Operating position	Horizontal only
	DVD-VR (CPRM compatible) DVD-R (SL/DL), DVD-RW, DVD-RAM	Dimensions (W x H x D)	17-1/10" x 2-6/8" x 13-13/16" (435 mm x 70 mm x 351 mm)
	AVCHD DVD-R (SL/DL), DVD-RW, DVD-RAM, SDHC, SD	Weight (net)	Approx. 5.3kg
	JPEG BD-RE (SL/DL), SDHC, SD, Everio backup disc (DVD-R/RW)		
	CD-DA Yes		
	Everio backup disc Yes		

*8: Only videos recorded using GY-HM series JVC camcorders in MOV format (Video Codec: MPEG2)
 *9: Only videos recorded using JVC camcorder GY-HM650/HM850 in MXF format (Video Codec: MPEG2)
 *10: Not compatible with Ver. 1.0 (23GB)
 *11: Direct recording possible in DVD-Video format using single sided single layer DVD-R disc. Dubbing from HDD is possible in DVD-Video format using single sided dual layer DVD-R disc.
 *12: Requires USB Card reader

DISCLAIMER: The recording of content on this device may require permission from the owner of the copyright or other such rights for that content. JVCKENWOOD has no authority to, does not grant permission, and explicitly disclaims any right, ability or intention to obtain such permission on the operator's behalf. It is the responsibility of the operator to ensure that the use of this device complies with any and all applicable copyright legislation.

E. & O.E. Design and specifications are subject to change without notice.
 "Blu-ray Disc" and "Blu-ray Disc" logo are trademarks. "AVCHD" and the "AVCHD" logo are trademarks of Panasonic Corporation and Sony Corporation. HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC. "Dolby" and the double-D symbol are trademarks of Dolby Laboratories. The i.LINK logo is a trademark of Sony Corporation. DTS is a registered trademark and the DTS logos, Symbol, DTS-HD and DTS-HD Master Audio Essential are trademarks of Digital Theater Systems, Inc. The SD and SDHC logos are trademarks of the SD Card Association. Java and all Java based trademarks and logos are trademarks or registered trademarks of Sun Microsystems, Inc. in the U.S. and other countries. All other brand or product names may be trademark and/or registered trademarks of their respective holders. Any rights not expressly granted herein are reserved.
 Copyright © 2015 JVCKENWOOD Corporation. All Rights Reserved.



DISTRIBUTED BY



Blu-ray Disc™ & HDD Recorder

SR-HD2700

Blu-ray Disc™ and HDD Combo Recorder featuring HD-SDI and HDMI Interfaces



KCS-8438

"JVC" is the trademark or registered trademark of JVCKENWOOD Corporation.


Introducing the Blu-ray Disc & HDD recorder with wider compatibility with digital sources, complete with HDMI and SDI input/output.

The SR-HD2700 is equipped with HDMI input in addition to HD/SD-SDI, enabling direct recording to Blu-ray disc or DVD from a variety of sources including video cameras and visual equipment, easily and efficiently. What's more, the ability to record simultaneously*1 to optical disc and HDD will streamline your workflow and enhance reliable recording.

*1: Simultaneous recording not possible with DVD-video and BDMV format discs.



Various applications and workflows for distributing video content



TV stations/Studios

Footage can be previewed immediately after recording at a studio or sports venue and a disc can be provided to the client on location. On-air program can be continuously recorded directly to disc and HDD up to 24 hours.



Concerts & Events

Events such as concerts, sporting events, and weddings can be burned to disc in real time while simultaneously recording to the HDD. It enables both quick delivery of disc and backup recording.




Production/Post Production

Edited video clip can be burned to BD or DVD with simple operation enabling you to create a check disc and dailies for clients and staff efficiently.



Educational Facilities

Lectures and seminars can be archived and provided to students. You can record directly from cameras and switchers with HDMI outputs.



High Performance Archiving/Recording via Digital Interfaces

HD-SDI and HDMI digital input/output



Digital input/output enables high quality HD archiving and recording with minimal loss. The SR-HD2700 is equipped with SDI terminals widely used in the broadcasting and post-production industry, plus HDMI input and output which are common on a wide range of digital products to deliver broad connectivity and system flexibility.

Direct-to-disc recording from live signals

The ability to record directly to disc in real-time improves efficiency by eliminating the process of recording to HDD and duplicating to disc. In addition, it enables downscaling and burning SD DVDs in real-time even when the input signal is HD.

Simultaneous optical disc & HDD recording

Simultaneous video recording*2 to optical disc and HDD is possible. It enables more versatile use for backup or multipurpose.

*2: Simultaneous recording not possible with DVD-video and BDMV format discs.



Long recording capability – up to 24H continuous recording

Continuous recording is possible to a maximum 24 hours (BD)*3 or 8 hours (DVD), or even longer up to full disc or HDD capacity with a short 30 second intermission. This capability is helpful in surveillance and monitoring applications as well as for checking on-air video content.

*3: Depending on the standard of the Blu-ray Disc being used, it may not be possible to record up to full capacity. When the maximum allowable recording time is reached, recording will stop momentarily and then resume as a separate file until the disc's capacity is reached.

Overlay text character for personalization and added security

It is possible to overlay characters*4 onto the image when recording signals input from SDI or HDMI, providing a deterrent for unauthorized usage and distribution of your original content.

*4: Alphanumeric characters and symbols are available.



Wide array of interfaces for flexible camera and video equipment connectivity

The front panel is equipped with SD/SDHC Card slot, i.LINK (HDV/DV IN) and USB terminals.

Input: HDMI, HD/SD-SDI, S-Video, Video, Audio (analog)
Output: HDMI, HD/SD-SDI, HD/SD-SDI through, Component video, S-Video, Video, Audio (analog)

All-in-one Recording, Simple Editing & Duplicating

Supports standard BD/DVD recording

BD-RE/BD-R, DVD-R and DVD-RW discs are supported for recording and playback. BD recording format support includes BDMV mode with menus*5 in addition to BDAV mode. DVD recording format support includes VR and Video modes. For playback, commercially available Blu-ray and DVD videos as well as music CDs are supported in addition to all those mentioned above.

*5: Menus are not supported when recording directly to disc in BDMV mode.


Simple editing functions without using a PC



Conveniently edit videos residing on the HDD without using a PC. You can easily create playlists, edit chapters and thumbnails, delete or split scenes, as well as edit the names of discs, titles and groups.

Flexible recording functions

Even without a PC, it is possible to copy HD video recordings directly onto a Blu-ray disc from an HD camcorder or down-convert them. In addition, direct-to-disc recording is also possible between HDD and disc. Content on HDD can be recorded to Blu-ray disc or down-converted to regular DVD with high picture quality.



Entire multiple discs dubbing function

An entire Blu-ray or DVD can be dubbed*6 to another blank disc, for distribution or various purposes.

*6: Some restrictions may apply.

RS-232C or LAN remote control and upload edited file from PC or Mac Computer

The SR-HD2700 is equipped with RS-232C and LAN terminals to enable remote operation with a computer. MOV and MXF files edited on an NLE system can be uploaded via LAN to SR-HD2700 for Blu-ray disc creation.

Other functions

- Max. 64X high-speed dubbing from internal HDD (1TB) to BD/DVD
- Creation of auto repeat playback discs
- Last function memory for duplication
- HDMI connectable to non-HDCP equipment

Recording times by mode

Rec mode	Picture quality	BD (SL)	BD (DL)	DVD (SL)	DVD (DL)	HDD (1TB)
HD	DR	1.9*7	3.8*7	—	—	80*7
	AF	4	8	—	—	160
	AN	6	12	—	—	252
	AL	9	18	—	—	378
	AE	12	24	—	—	504
	XP	5.25	10.5	1	1.7	220
SD	SP	10.5	21	2	3.5	444
	LP	21	42	4	7.1	884
	EP	42	84	8	14.3	1774
	DR1	1.8	3.6	—	—	76
	DR2	2	4	—	—	84
	DR3	2.9	6	—	—	124
DR4	3.9	7.8	—	—	164	

*7: Reference figure for importation of HDV.